




配光特性

図番 MR150202



カタログ番号	X141BN
オプション番号	3000K Ra85
使用ランプ	XTM19803030CCA
ランプ光束	3000.0 lm 1,000
器具効率	94.4 %
下方効率	94.4 %
上方効率	0.0 %
最大取付間隔	
A断面	0.68 H
C断面	
B断面	

X-series4.0 BASE	角度	光度
	0°	4876
	10°	4096
	20°	2687
	30°	1328
	40°	281
	50°	3
	60°	5
	70°	8
	80°	16
	90°	4
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
	170°	0
	180°	0



照 明 率 表		平均照度=台数×照明率×保守率× 3000 (光束)/(間口×奥行)											
床面反射率(%)		20											
天井面反射率(%)		0											
壁面反射率(%)		0											
室	0.50	0.66	0.61	0.58	0.65	0.61	0.58	0.65	0.61	0.58	0.64	0.60	0.58
	0.70	0.76	0.71	0.68	0.75	0.71	0.68	0.74	0.70	0.67	0.73	0.70	0.67
	1.00	0.85	0.80	0.77	0.83	0.79	0.76	0.82	0.78	0.76	0.80	0.77	0.75
	1.25	0.89	0.85	0.82	0.87	0.84	0.81	0.86	0.82	0.80	0.84	0.81	0.79
	1.50	0.93	0.88	0.85	0.90	0.87	0.84	0.88	0.85	0.83	0.86	0.84	0.82
	2.00	0.97	0.93	0.90	0.94	0.91	0.88	0.91	0.89	0.87	0.89	0.87	0.85
	2.50	0.99	0.96	0.93	0.96	0.94	0.91	0.93	0.91	0.89	0.91	0.89	0.87
	3.00	1.01	0.98	0.95	0.98	0.95	0.93	0.95	0.93	0.91	0.92	0.90	0.89
	4.00	1.04	1.01	0.99	1.00	0.98	0.96	0.96	0.95	0.93	0.93	0.92	0.91
	5.00	1.05	1.03	1.01	1.01	1.00	0.98	0.98	0.96	0.95	0.94	0.93	0.92
数	7.00	1.07	1.05	1.04	1.03	1.01	1.00	0.99	0.98	0.97	0.95	0.94	0.94
	10.00	1.08	1.07	1.06	1.04	1.03	1.02	1.00	0.99	0.98	0.96	0.95	0.95