

配光特性


図番 MR140327





カタログ番号	J520CN
オプション番号	3500K Ra85 暫定値
使用ランプ	BLM-1120-35853-00
ランプ光束	4100.0 lm 1,000
器具効率	67.4 %
下方効率	67.4 %
上方効率	0.0 %
最大取付間隔	
A断面	0.94 H
C断面	
B断面	

角度	光度
	0°
10°	3882
20°	3604
30°	3186
40°	1445
50°	74
60°	6
70°	1
80°	0
90°	0
100°	1
110°	0
120°	0
130°	0
140°	0
150°	0
160°	0
170°	0
180°	0

G.E.M. DL-BASE 暫定値



断面



照 明 率 表		平均照度=台数×照明率×保守率×4100(光束)/(間口×奥行)											
床面反射率(%)		20											
天井面反射率(%)		0											
壁面反射率(%)		0											
室 指 数	0.50	0.47	0.44	0.42	0.47	0.44	0.42	0.46	0.44	0.42	0.46	0.43	0.41
	0.70	0.55	0.51	0.49	0.54	0.51	0.49	0.53	0.51	0.49	0.53	0.50	0.47
	1.00	0.61	0.58	0.56	0.60	0.57	0.55	0.59	0.56	0.55	0.58	0.56	0.53
	1.25	0.64	0.61	0.59	0.63	0.60	0.58	0.61	0.59	0.58	0.60	0.58	0.56
	1.50	0.66	0.64	0.61	0.65	0.62	0.61	0.63	0.61	0.60	0.62	0.60	0.58
	2.00	0.69	0.67	0.65	0.67	0.65	0.64	0.66	0.64	0.62	0.64	0.63	0.61
	2.50	0.71	0.69	0.67	0.69	0.67	0.66	0.67	0.66	0.64	0.65	0.64	0.63
	3.00	0.72	0.70	0.69	0.70	0.68	0.67	0.68	0.67	0.65	0.66	0.65	0.64
	4.00	0.74	0.73	0.71	0.72	0.70	0.69	0.69	0.68	0.67	0.67	0.66	0.65
	5.00	0.75	0.74	0.73	0.72	0.71	0.70	0.70	0.69	0.68	0.67	0.67	0.66
数	7.00	0.76	0.75	0.74	0.73	0.73	0.72	0.71	0.70	0.69	0.68	0.68	0.67
	10.00	0.77	0.77	0.76	0.74	0.74	0.73	0.71	0.71	0.70	0.69	0.68	0.68