

Luminaire

Code AF10201+AF95204
 Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Measur.

Code FTS1603148
 Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK


Luminaire Flux	713.68 lm	Luminaire Power	11.00 W	Efficacy	64.88 lm/W	Efficiency	100.00%
Lamps Flux	713.68 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	150 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	148 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.005476 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001325 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		713.68 lm	

LED Flux=996,2lm LED Power=11W Eff=72% EfcLed=91lm/W EfcLum=65lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 100 100
 F UTE --

D DIN 5040
 B NBN
 A60
 BZ 1


150mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code AF10201+AF95204
Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Measurerm.

Code FTS1603148
Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	713.68 lm	Luminaire Power	11.00 W	Efficacy	64.88 lm/W	Efficiency	100.00%
Lamps Flux	713.68 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	150 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	148 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area	0.005476 m2	Emitting area on Plane 180°		Emitting area on Plane 270°		Emitting area on Plane 90°	0.001325 m2
Emitting area on Plane 0°	0.000000 m2	Glare area at 76°					
Emitting area on Plane 90°	0.000000 m2						
Coordinate system	CG	Symmetry Type		Maximum Gamma Angle		Measurement Flux	
Date	17-07-2017						
Measurement Distance	0.00						


LED Flux=996,2lm LED Power=11W Eff=72% EfcLed=91lm/W EfcLum=65lm/W CCT=2700K Ra=90 SDCM=2 L90(20K)=118000h

C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00
OB	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00
OC	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00
OD	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	1021	616		
2.00	1.96	255	154		
3.00	2.93	113	68		
4.00	3.91	64	39		
5.00	4.89	41	25		