



配光特性

図番 MR140401

カタログ番号	T501AB
オプション番号	2700K Ra80
使用ランプ	LXR8-SW27
ランプ光束	1117.0 lm 1.000
最大光度	3020.4 cd
1/2ビーム角	
A断面	25.80 °
C断面	
B断面	



G.E.M. 60SPOT	角度	光度
	0°	3020
	10°	2002
	20°	604
	30°	133
	40°	19
	50°	4
	60°	0
	70°	0
	80°	0
	90°	0
	100°	0
	110°	0
	120°	0
	130°	0
	140°	0
	150°	0
	160°	0
	170°	0
	180°	0



照 明 率 表		平均照度=台数×照明率×保守率×1117(光束)/(間口×奥行)											
床面反射率(%)		20											
天井面反射率(%)		0											
壁面反射率(%)		0											
室	0.50	0.57	0.54	0.53	0.56	0.54	0.52	0.56	0.54	0.52	0.55	0.54	0.52
	0.70	0.61	0.59	0.57	0.61	0.58	0.57	0.60	0.58	0.57	0.59	0.58	0.56
	1.00	0.66	0.63	0.61	0.65	0.62	0.61	0.64	0.62	0.60	0.63	0.61	0.59
	1.25	0.68	0.65	0.64	0.67	0.65	0.63	0.65	0.64	0.62	0.64	0.63	0.60
	1.50	0.69	0.67	0.65	0.68	0.66	0.64	0.66	0.65	0.64	0.65	0.64	0.62
	2.00	0.72	0.70	0.68	0.70	0.68	0.67	0.68	0.67	0.65	0.66	0.65	0.63
	2.50	0.73	0.71	0.70	0.71	0.69	0.68	0.69	0.68	0.67	0.67	0.66	0.64
	3.00	0.74	0.72	0.71	0.72	0.70	0.69	0.69	0.68	0.67	0.67	0.67	0.64
	4.00	0.75	0.74	0.73	0.73	0.72	0.71	0.70	0.69	0.69	0.68	0.67	0.65
	5.00	0.76	0.75	0.74	0.73	0.72	0.72	0.71	0.70	0.69	0.68	0.68	0.65
数	7.00	0.77	0.76	0.75	0.74	0.73	0.73	0.71	0.71	0.70	0.69	0.68	0.66
	10.00	0.78	0.77	0.77	0.75	0.74	0.74	0.72	0.71	0.71	0.69	0.69	0.66