

配光特性


図番 MB-WW/BB-H

カタログ番号	YDT48M(B/W)		
使用ランプ	LED/3500K		
ランプ光束	1430.0	lm	1,000
最大光度	5830	cd	
1/2ビーム角			
A断面	28.00 °		
C断面			
B断面			





角度	光度
	0°
10°	5830
20°	4774
30°	686
40°	189
50°	64
60°	9
70°	4
80°	1
90°	1
100°	0
110°	0
120°	0
130°	0
140°	0
150°	0
160°	0
170°	0
180°	0

SALIOT™
φ175 ユニバーサルダウンライト



断面



照 明 率 表		平均照度=台数 * 照明率 * 保守率 * 1430 (光束)/(間口 * 奥行)												
床面反射率(%)		20												0
天井面反射率(%)		80			60			40			20			0
壁面反射率(%)		50	30	10	50	30	10	50	30	10	50	30	10	0
室	0.50	0.89	0.86	0.83	0.88	0.85	0.83	0.88	0.85	0.83	0.87	0.85	0.83	0.82
	0.70	0.95	0.91	0.89	0.94	0.91	0.89	0.93	0.90	0.88	0.92	0.90	0.88	0.87
	1.00	1.01	0.97	0.94	0.99	0.96	0.94	0.97	0.95	0.93	0.96	0.94	0.92	0.91
	1.25	1.03	1.00	0.97	1.01	0.99	0.96	1.00	0.97	0.95	0.98	0.96	0.94	0.93
	1.50	1.06	1.02	1.00	1.03	1.01	0.98	1.01	0.99	0.97	0.99	0.97	0.96	0.94
指	2.00	1.09	1.06	1.03	1.06	1.03	1.01	1.03	1.01	1.00	1.01	0.99	0.98	0.96
	2.50	1.10	1.08	1.06	1.07	1.05	1.03	1.04	1.03	1.01	1.02	1.00	0.99	0.97
	3.00	1.12	1.09	1.07	1.08	1.06	1.05	1.05	1.04	1.02	1.02	1.01	1.00	0.97
	4.00	1.14	1.12	1.10	1.10	1.08	1.07	1.06	1.05	1.04	1.03	1.02	1.01	0.98
	5.00	1.15	1.13	1.12	1.11	1.09	1.08	1.07	1.06	1.05	1.03	1.03	1.02	0.99
数	7.00	1.16	1.15	1.14	1.12	1.11	1.10	1.08	1.07	1.06	1.04	1.03	1.03	0.99
	10.00	1.17	1.16	1.16	1.13	1.12	1.11	1.08	1.08	1.07	1.04	1.04	1.04	1.00