

Luminaire

Code M330620

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 2700K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO


Measurement

Code FTS1602730

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 2700K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	974.89 lm	Luminaire Power	13.00 W	Efficacy	74.99 lm/W	Efficiency	100.00%
Lamps Flux	974.89 lm	Maximum value	2741.50 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area	Length Diam.	80 mm 50 mm	Width Height	80 mm 0 mm	Height	115 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.001963 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.000475 m2				
Coordinate system Date Measurement Distance	CG 09-04-2015 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 90 974.89 lm				
LED Flux=1330lm LED Power=13W Eff=73,3% EfcLed=102lm/W EfcLum=75lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	97 100 100 100 100 --	D DIN 5040 B NBN	A60 BZ 1				


80mm x 80mm



Semipiani C

180.0 — 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code M330620
Name EVERYTHING 80 QUADRATO TRIM FISSO LED 2700K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Measurement


Code FTS1602730
Name EVERYTHING 80 QUADRATO TRIM FISSO LED 2700K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	974.89 lm	Luminaire Power	13.00 W	Efficacy	74.99 lm/W	Efficiency	100.00%
Lamps Flux	974.89 lm	Maximum value	2741.50 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area	Length Diam.	80 mm 50 mm	Width Height	80 mm 0 mm	Height	115 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.001963 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.000475 m2				
Coordinate system Date Measurement Distance	CG 09-04-2015 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 90 974.89 lm				
LED Flux=1330lm LED Power=13W Eff=73,3% EfcLed=102lm/W EfcLum=75lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	97 100 100 100 100 --	D DIN 5040 B NBN	A60 BZ 1				

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.27	0.53	0.80	1.07	1.33	OC	0.27	0.53	0.80	1.07	1.33
OB	0.27	0.53	0.80	1.07	1.33	OD	0.27	0.53	0.80	1.07	1.33

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2672.66	2426.52	1327.63	542.47	171.45	39.55	1.23	0.00	0.00	0.00
OB	2672.66	2426.52	1327.63	542.47	171.45	39.55	1.23	0.00	0.00	0.00
OC	2672.66	2426.52	1327.63	542.47	171.45	39.55	1.23	0.00	0.00	0.00
OD	2672.66	2426.52	1327.63	542.47	171.45	39.55	1.23	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=14.9°+14.9°	G=0.0
1.00	0.53	2673	1614		
2.00	1.07	668	403		
3.00	1.60	297	179		
4.00	2.13	167	101		
5.00	2.66	107	65		