



# 配光特性

図番 YL210029



|        |                                |
|--------|--------------------------------|
| カタログ番号 | J602BN                         |
| 使用ランプ  |                                |
| 器具光束   | 1868.0 lm <small>1.000</small> |
| 器具効率   | 100.0 %                        |
| 下方効率   | 100.0 %                        |
| 上方効率   | 0.0 %                          |
| 最大取付間隔 |                                |
| A断面    | 0.82 H                         |
| C断面    |                                |
| B断面    |                                |

|      |      |      |
|------|------|------|
|      | 角度   | 光度   |
|      | 0°   | 2947 |
|      | 10°  | 2821 |
|      | 20°  | 2266 |
|      | 30°  | 573  |
|      | 40°  | 66   |
|      | 50°  | 23   |
|      | 60°  | 18   |
|      | 70°  | 16   |
|      | 80°  | 13   |
|      | 90°  | 12   |
|      | 100° | 0    |
|      | 110° | 0    |
|      | 120° | 0    |
|      | 130° | 0    |
|      | 140° | 0    |
|      | 150° | 0    |
|      | 160° | 0    |
| 170° | 0    |      |
| 180° | 0    |      |



| 照明率表       |      | 平均照度=台数×照明率×保守率×1868(光束)/(間口×奥行) |      |      |      |      |      |      |      |      |      |      |      |      |
|------------|------|----------------------------------|------|------|------|------|------|------|------|------|------|------|------|------|
| 床面反射率 (%)  |      | 20                               |      |      |      |      |      |      |      |      |      |      |      |      |
| 天井面反射率 (%) |      | 80                               |      |      | 60   |      |      | 40   |      |      | 20   |      |      |      |
| 壁面反射率 (%)  |      | 50                               | 30   | 10   | 50   | 30   | 10   | 50   | 30   | 10   | 50   | 30   | 10   |      |
| 室          | 0.50 | 0.72                             | 0.67 | 0.63 | 0.71 | 0.66 | 0.63 | 0.70 | 0.66 | 0.63 | 0.69 | 0.66 | 0.63 |      |
|            | 0.70 | 0.82                             | 0.77 | 0.73 | 0.81 | 0.76 | 0.73 | 0.79 | 0.76 | 0.73 | 0.78 | 0.75 | 0.72 |      |
|            | 1.00 | 0.91                             | 0.86 | 0.82 | 0.89 | 0.85 | 0.82 | 0.87 | 0.84 | 0.81 | 0.86 | 0.83 | 0.80 |      |
|            | 1.25 | 0.95                             | 0.91 | 0.87 | 0.93 | 0.89 | 0.86 | 0.91 | 0.88 | 0.85 | 0.89 | 0.86 | 0.84 |      |
|            | 1.50 | 0.98                             | 0.94 | 0.91 | 0.96 | 0.92 | 0.89 | 0.94 | 0.91 | 0.88 | 0.92 | 0.89 | 0.87 |      |
|            | 指    | 2.00                             | 1.03 | 0.99 | 0.96 | 1.00 | 0.97 | 0.94 | 0.97 | 0.94 | 0.92 | 0.94 | 0.92 | 0.90 |
|            |      | 2.50                             | 1.05 | 1.02 | 0.99 | 1.02 | 0.99 | 0.97 | 0.99 | 0.97 | 0.95 | 0.96 | 0.94 | 0.93 |
|            |      | 3.00                             | 1.07 | 1.04 | 1.02 | 1.04 | 1.01 | 0.99 | 1.00 | 0.98 | 0.97 | 0.97 | 0.96 | 0.94 |
|            |      | 4.00                             | 1.10 | 1.07 | 1.05 | 1.06 | 1.04 | 1.02 | 1.02 | 1.01 | 0.99 | 0.99 | 0.98 | 0.97 |
|            | 数    | 5.00                             | 1.12 | 1.09 | 1.07 | 1.07 | 1.06 | 1.04 | 1.04 | 1.02 | 1.01 | 1.00 | 0.99 | 0.98 |
| 7.00       |      | 1.14                             | 1.12 | 1.10 | 1.09 | 1.08 | 1.06 | 1.05 | 1.04 | 1.03 | 1.01 | 1.00 | 0.99 |      |
| 10.00      |      | 1.15                             | 1.14 | 1.13 | 1.10 | 1.09 | 1.08 | 1.06 | 1.05 | 1.04 | 1.02 | 1.01 | 1.01 |      |